

## SC-396/506



### Feature:


- CFC free refrigeration system
- Automatic defrosting
- Hot air prevents condensation
- Air cycled enforced by fan
- Back-lit canopy for branding & advertising
- Total door frame
- Adjustable shelves
- Lock pad
- Four direction swivel castors with braker
- Adjustable feet

### Optional:

- Side panes & Canopy graphics
- Price strips
- Canopy light switch
- Energy management system




CFC free




Self-closing door




Interior fan for ventilation



Reversed door opening design



Adjustable shelves



Excellent heat preservation tech



Price strip on shelf design



One piece of door frame

# Specification



Model of product		Unit	SC-396	SC-506	
<b>Technical Data</b>					
Gross Volume		L/ft3	418/14.8	528/18.6	
Net Volume		L/ft3	396/14	506/17.8	
Gross Weight		Kg/Pound	116/254	137/300	
Net Weight		Kg/Pound	112/246	133/292	
Shelves Number		EA	4	4	
Pack-out	355ml Can	Facing	Can	8	10
		Depth	Can	6	6
		Layer	Can	8	8
		Total	Can	384	480
	20oz PET Bottle	Facing	Bottle	8	8
		Depth	Bottle	6	6
		Layer	Bottle	5	5
		Total	Bottle	192	240
Climate Class		/	ST	ST	
Certificate		/	CCC	CCC	
Temperature Range		°C/°F	0-10/32-50	0-10/32-50	
<b>Electrical Data</b>					
Rated Voltage/Frequency		/	220V/50Hz	220V/50Hz	
Rated Power		W	400	600	
Rated Electric Current		A	3	4	
<b>Refrigeration Data</b>					
Refrigerant		/	R134a	R134a	
Foaming Agent		/	C-P/I-P	C-P/I-P	
<b>Dimensions</b>					
External Dimensions (W×D×H)		mm	675*660*2276	835*660*2276	
		/inch	26.6*26*89.6	32.8*26*89.6	
Packaging Dimensions (W×D×H)		mm	745*760*2330	915*760*2330	
		/inch	29.3*30*91.7	36*30*91.7	
Stuffing Quantity (20')		Set	24	18	
Stuffing Quantity (40')		Set	48	39	
Stuffing Quantity (40'H)		Set	48	39	
Optional	Refrigerant	/	-	-	
	Voltage/Frequency	/	-	-	