

SC-600GA/1100GA



Feature:


- CFC free refrigeration system
- Back-lit canopy for branding & advertising
- Aluminium door frame
- Low-E and argon filled triple panes (D Condition) glass door
- Adjustable shelves
- EMS controller
- Cassette refrigeration system
- LED light
- Four direction swivel castors with braker
- Adjustable feet

Optional:

- Side panes & Canopy graphics
- Price strips (SC-1100GA)
- Surge protector
- Adjustable shelves
- Visi slide




CFC free



Cassette refrigerant




Bottle opener



Self-closing door



Excellent EMS control



Reversed door opening design



Price strip on shelf design



Steel door frame & compressor front cover



Visi slide

Specification



Model of product		Unit	SC-600GA	SC-1100GA		
Technical Data						
Gross Volume		L/ft ³	605/21.4	1200/42.4		
Net Volume		L/ft ³	550/19.4	1100/39		
Gross Weight		Kg/Pound	170/373	252/553		
Net Weight		Kg/Pound	167/366	250/548		
Shelves Number		EA	5	10		
Pack-out	355ml Can	Facing	Can	9	16	
		Depth	Can	7	7	
		Layer	Can	10	10	
		Total	Can	630	1120	
	20oz PET Bottle	Facing	Bottle	8	16	
		Depth	Bottle	7	7	
		Layer	Bottle	5	5	
		Total	Bottle	280	560	
		Climate Class		/	N(C condition)	T(C/D condition)
		Certificate		/	SAA	SAA
Temperature Range		°C/°F	0-7.2/32-44.9	0-7.2/32-44.9		
Electrical Data						
Rated Voltage/Frequency		/	220-240V/50Hz	220-240V/50Hz		
Rated Power		W	500	900		
Rated Electric Current		A	3.6	6.8		
Refrigeration Data						
Refrigerant		/	R134a	R134a		
Foaming Agent		/	C-P/I-P	C-P/I-P		
Dimensions						
External Dimensions (W×D×H)		mm	640*774*2198	1280*774*2198		
		inch	25.2*30.5*86.5	50.4*30.5*86.5		
Packaging Dimensions (W×D×H)		mm	660*827*2200	1290*780*2200		
		inch	26*32.6*86.6	50.8*30.7*86.6		
Stuffing Quantity (20')		Set	21	12		
Stuffing Quantity (40')		Set	45	24		
Stuffing Quantity (40'H)		Set	45	24		
Optional	Refrigerant	/	-	-		
	Voltage/Frequency	/	-	-		