

## SD-242/332



### Feature:

- Attractive curved appearance
- Rohs compliance
- One piece top frame(SD-332)
- Aluminum inner liner
- Low-E toughened glass lid
- 4 casters
- Quiet operation

### Optional:

- Four side graphics
- Electronic & Analog thermometer
- Safety door lock
- Mesh basket & partition
- Power off alarm
- Effective compressor
- IQ Fan
- Inner front LED light
- Caster breaker
- Big scoop
- RFID
- Anti-mouse cable




CFC free



Lock



Anti-rust



Thick foam



Electronic & mechanical thermometer



Large single casters



Inner LED light



Powder coated baskets and dividers

# Specification



Model of product	Unit	SD-242	SD-332
<b>Technical Data</b>			
Gross Volume	L/ft3	242/8.6	332/11.7
Net Volume	L/ft3	180/6.4	260/9.2
Gross Weight	Kg/Pound	67/147	80/176
Net Weight	Kg/Pound	57/125	72/158
Baskets Number	EA	4	5
Ambient Temperature	°C /°F	16-35/60.8-95	16-35/60.8-95
Certificate	/	CCC	CCC/CE/GS
Temperature Range	°C /°F	-14 ~ -23/6.8 ~ -9.4	-14 ~ -23/6.8 ~ -9.4
<b>Electrical Data</b>			
Voltage/Frequency	/	220-240V/50Hz	220-240V/50Hz
Rated Power	W	200	220
Rated Electric Current	A	1.6	2.0
<b>Refrigeration Data</b>			
Refrigerant	/	R134a	R134a
Foaming Agent	/	CP-IP	CP-IP
<b>Dimension Data</b>			
External Dimensions (W*D*H)	mm	1004*634*880	1204*634*916
	inch	39.5*25*34.6	47.4*25*36
Packaging Dimensions (W*D*H)	mm	1090*770*945	1290*770*950
	inch	43*30.3*37.2	50.7*30.3*37.4
Stuffing Quantity (20')	Set	30	26
Stuffing Quantity (40')	Set	66	54
Stuffing Quantity (40HC)	Set	66	54
Optional configuration	Refrigerant Optional	R290	R290
	Voltage/Frequency	-	220V/60Hz