

SD-55/95



Feature:

- CFC free
- Attractive arc appearance
- Rohs compliance
- One piece top frame sealed design
- Self closing door design
- One piece top frame(SD-95)
- Aluminum inner liner
- Quiet operation
- Low-E toughened glass lid
- 4 adjustable feet

Optional:

- Four side graphics
- Safety door lock
- Big scoop
- RFID




CFC free




Lock



Anti-rust



Thick foam



One piece top frame design

Specification



Model of product	Unit	SD-55	SD-95
Technical Data			
Gross Volume	L/ft3	67/2.4	95/3.4
Net Volume	L/ft3	55/1.9	78/2.8
Gross Weight	Kg/Pound	55/121	60/132
Net Weight	Kg/Pound	50/110	55/121
Baskets Number	EA	2	2
Ambient Temperature	°C /°F	16-30/60.8-86	16-30/60.8-86
Certificate	/	CCC/CE	CCC
Temperature Range	°C /°F	-14 ~ -23/6.8 ~ -9.4	-14 ~ -23/6.8 ~ -9.4
Electrical Data			
Voltage/Frequency	/	220-240V/50Hz	220-240V/50Hz
Rated Power	W	175	195
Rated Electric Current	A	1.9	1.9
Refrigeration Data			
Refrigerant	/	R134a	R134a
Foaming Agent	/	CP-IP	CP-IP
Dimension Data			
External Dimensions (W*D*H)	mm	595*508*615	595*560*845
	inch	23.4*20*24.2	23.4*22*33.3
Packaging Dimensions (W*D*H)	mm	665*580*660	676*626*895
	inch	26.2*22.8*26	26.6*24.7*35.2
Stuffing Quantity (20')	Set	105	54
Stuffing Quantity (40')	Set	204	114
Stuffing Quantity (40HC)	Set	272	170
Optional configuration	Refrigerant Optional	-	-
	Voltage/Frequency	-	-