



Hot&cold

KIKKO MAX





Kikko Max is the free standing vending machine with a 620 cup capacity and up to 7 canisters which complements the Necta Hot & Cold range. With a height of 1830 mm, it has been designed to stand alongside the similarly sized Snakky Max or Sfera machines. The Kikko Max works in a master/slave mode and utilizes a single payment system which provides "One-Stop-Shopping" and creates an appealing machine bank, ensuring the most user friendly and practical vending service available.

ELECTRONIC CONTROL

The 16-bit electronic control with incorporated flash EPROM is extremely flexible and complete, as well as being compatible with the PC application GIGA. This allows a palmtop to be connected, via an RS232 interface, to allow the automatic set-up of the machine as well as the downloading of sales statistics and data (also in EVA-DTS format). With GIGA it is also possible to have remote monitoring of the machine using GSM technology.

PAYMENT SYSTEMS

Kikko Max is pre-set for the installation of systems with Executive, BDV and MDB protocol as well as for installation of validators.

At the same time, the following can be fitted:

- Change-giver, validator or coin mechanism
- Bill acceptor
- Cashless system with key or card.

ACCESSORIES

Mechanical selections counter kit
Lid for coin box kit
Cup sensor + cup station lamp kit
Cup station lamp kit
20 litre water tank kit
2x20 litre water tanks kit
Still cooling unit kit (for powders)
Master/slave kit
RS232 jack kit
GSM kit



Optimum internal access
Z 3000 patented coffee group

POWER CONSUMPTION

Espresso version To reach operating temperature For each hour of stand-by	51.71 Wh 100 Wh
Instant version To reach operating temperature For each hour of stand-by	174.1 Wh 88.7 Wh

CAPACITY

Cups (Ø 70-71 mm)	620*
Stirrers (length 95/105 mm)	550
Containers	6 ES / 7 IN
Espresso boiler	0.6 l
Instant boiler	2 l
Coffee beans	3.2 kg
Instant coffee	0.9 kg ES / 1.2 kg IN
Chocolate	5.2 kg
Milk	2.6 kg
Tea	3.2 kg
Sugar	4 kg

*166 cc

CHARACTERISTICS

Height	1830 mm*
Width	540 mm
Depth	650 mm
Overall depth with door open	1120 mm
Weight	126 kg ca.
Power supply voltage	230 V
Power supply frequency	50 Hz
Installed power	1800 W
Water mains pressure (With 3/4" gas male connection)	0.5 to 8.5 bar

*Adjustable feet: +10 -10 mm



EXAMPLES OF POSSIBLE CONFIGURATIONS

	KIKKO MAX ES 6 (Espresso Unit + 5 canisters)	KIKKO MAX IN 7 (7 canisters)
Pre-selections		
Sugar dosing	☕	☕
Bean coffee black	☕	
Bean coffee long	☕	
Bean café au lait	☕	
Bean coffee white	☕	
Instant espresso coffee		☕
Coffee long		☕
Café au lait		☕
Coffee white		☕
Cappuccino	☕	☕
Chocolate	☕	☕
Chocolate strong	☕	☕
Chocomilk	☕	☕
Decaf/Instant coffee black	☕	☕
Decaf/Instant coffee long	☕	☕
Decaf/Instant café au lait	☕	☕
Decaf/Instant cappuccino	☕	☕
Lemon tea	☕	☕
Soup		☕
Milk/Hot water	☕	☕
Cup only	☕	☕
No cup	☕	

N&W GLOBAL VENDING S.p.A.

Via Roma, 24
24030 Valbrembo (BG) Italy
Tel. +39 035 606111 - Fax +39 035 606519

www.nwglobalvending.com

