

technical data sheet GPE 50

Gpe Vendors via Toniolo 19/21 - 61032 Fano (PU) - Tel +39 0721.854535 - Fax +39 0721.855200 - www.gpevendors.it - gpe@vendors.it

CONFIGURATION

Configuration standard and on request

SPIRALS

In steel; models available on Layout page

LIGHTING

LED

GRAPHIC DISPLAY

Pogrammable in different languages with various spot possibilities, Programmable stand-by.

CHILLER

Compact chiller for quick and easy extraction. Ecological refrigeration Gas R404A. Internal Temperature 8°C with external temperature at 32°C. 3°C Version.

Optional Quiet Chiller.
Programmable Stand-by

FRONT GLASS

Excellent product visibility

TECHNOLOGY

Telemetry; applicable internet Modem; EVA-DTS, GPE DATA (software updating by PC)

PAYMENT SYSTEM

Executive – MDB; predisposed for latest generation payment systems (credit card, Paypal,...)



DIMENSIONS

HEIGHT WIDTH DEPTH WEIGHT 183 cm 94,5 cm 82,5 cm 240 kg

ELECTRIC POWER SUPPLY ABSORBED POWER

0,4 Kw

230V +/- 10% Also possible in 110V version

STANDARD VERSION

3C° VERSION





GPE